



Professional tester providing highly accurate measurements.

FEATURES

- **Battery 6 and 12 V** : test the voltage and the state of charge.
- **Starter 12 and 24 V** : test the start voltage.
- **Alternator 12 and 24 V** : tests no load voltage and charging voltage as well as current undulation during the charge.

INSTANT ANALYSIS

- Battery voltage (1.5 V to 30 V)
- Available starting power
- Charge state and battery health (%)

BATTERY TYPES

- Compatible with multiple types of lead-acid battery ranging from 7 to 230 Ah :
 - VRLA / GEL / AGM FLAT / AGM SPIRAL sealed batteries
 - STANDARD LIQUID batteries
 - START / STOP batteries (EFB/AGM)

■ Operating range :

- EN : 40 > 2100 CCA
- DIN : 25 > 1300 CCA
- SAE : 40 > 2000 CCA
- JIS : Japanese battery
- IEC : 30 > 1500 CCA (international standard)
- CA/MCA : 50 > 2500 CCA (marine battery)



Supplied with a carry case

HIGHLY ACCURATE

- Automatic compensation for external temperature.
- Advanced dynamic resistance measurement technology minimises battery discharge and displays an accurate result which is unaffected by :
 - the surface charge
 - parasitic load (lights, various indicators, etc)
 - contact imperfections (worn out terminals/ lugs, unfastened lugs, etc)

PRACTICAL

- LCD backlit display
- Multi-lingual interface
- Removable clamps
- Protection against polarity reversal
- ABS case (acid resistant) and protection against shock.
- Power supply: 6 x 1.5V internal batteries supplied (type LR6 – AA)

		TEST			RESULT		TEMPERATURE COMPENSATION	mm	kg	
Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE								
6-12 V	7 >230 Ah	•	• min 1.5 V	12 V 24 V	1 s	instant	•	190 x 50 x 115	180 cm	0.8